

Material Safety Data Sheet

PRODUCT IDENTITY: PC-150 Comparable to DuPont© Binder

anufacturer Name: Performance Products		NFPA Ratings		
Address: PO Box 463			Health	2
Lansing IL 60438				
elephone for information: 866-228-6528			Flammability	3
			Reactivity	0
Emergency Telephone: Chemtrec 800-2	62-8200		Personal	
			Protection	G
Section II-Hazardous Ingredients	/Identity Informati	on		_
lazardous Components (Specific Chemic	al Identity Common Na	amo)		
lazardous components (Specific Chemic	CAS#	OSHA PEL	ACGIH TLV	Wt %
TOLUENE	<u>108-88-3</u>	100 ppm	100 ppm	15/20
XYLENE	1330-20-7	100 ppm	100 ppm	20/25
BUTYL ACETATE	123-86-4	150 ppm	150 ppm	10/15
	108-65-6	Not est.	Not est.	1/5
EHTYL BENZENE	100-41-4	100 ppm	100 ppm	1/5
-PROPANOL	67-63-0	400 ppm	400 ppm	1/5
THYL ACETATE	141-78-6	100 ppm	100 ppm	1/5
CETONE	67-64-1	750 ppm	750 ppm	5/10
M&P NAPHTHA	8032-32-4	200 ppm	200 ppm	10/15
SARA 313 listed chemical				
	AINT RELATED MATE	RIAL		
OOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F 'apor Density (Air = 1): Heavier than Air	aracteristics Specific Gravity (H20 = Evaporation Rate:(but	= 1): 0.88 Va yl acetate = 1) >1 V	apor Pressure (mm⊦ .O.C.: 6.51 #/gal	
OOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F /apor Density (Air = 1): Heavier than Air	aracteristics Specific Gravity (H20 = Evaporation Rate:(but	= 1): 0.88 Va yl acetate = 1) >1 V		
DOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F /apor Density (Air = 1): Heavier than Air Appearance and Odor: Clear Liquid, Solve Section IV-Fire and Explosion Ha	Specific Gravity (H20 = Evaporation Rate:(but ent Odor	= 1): 0.88 Va yl acetate = 1) >1 V	.O.C.: 6.51 #/gal	
OOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F /apor Density (Air = 1): Heavier than Air Appearance and Odor: Clear Liquid, Solve Section IV-Fire and Explosion Ha	Specific Gravity (H20 = Evaporation Rate:(but) ent Odor	= 1): 0.88 Va yl acetate = 1) >1 V	.O.C.: 6.51 #/gal O.C. less exempt s	
OOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F (apor Density (Air = 1): Heavier than Air Appearance and Odor: Clear Liquid, Solve Section IV-Fire and Explosion Ha	Specific Gravity (H20 = Evaporation Rate:(but) ent Odor	= 1): 0.88 Va yl acetate = 1) >1 V V.	.O.C.: 6.51 #/gal O.C. less exempt s	
OT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F (apor Density (Air = 1): Heavier than Air Appearance and Odor: Clear Liquid, Solve Section IV-Fire and Explosion Ha	Specific Gravity (H20 = Evaporation Rate:(but) ent Odor Azard Data Flammable Limits	= 1): 0.88 Va yl acetate = 1) >1 V V. s: LEL 1.0 UEL 15	.O.C.: 6.51 #/gal O.C. less exempt s .0	
DOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F Yapor Density (Air = 1): Heavier than Air Appearance and Odor: Clear Liquid, Solve Section IV-Fire and Explosion Ha Flash Point (Method Used): <20°F (TCC) Extinguishing Media Class B extinguisher, Carbon Dioxid Water spray can be used to cool cor self-contained breathing apparatus a	Aracteristics Specific Gravity (H20 = Evaporation Rate:(but) ent Odor Azard Data Flammable Limits e, Dry Chemical, Foam itainers exposed to fire.	= 1): 0.88 Va yl acetate = 1) >1 V V. s: LEL 1.0 UEL 15 Special Fire Fighting F Clear area of unprote	.O.C.: 6.51 #/gal O.C. less exempt s .0 Procedures cted personnel. Fire	olvents: 5.9 #/gal
DOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F Yapor Density (Air = 1): Heavier than Air Appearance and Odor: Clear Liquid, Solve Section IV-Fire and Explosion Ha Flash Point (Method Used): <20°F (TCC) Extinguishing Media Class B extinguisher, Carbon Dioxid Water spray can be used to cool cor self-contained breathing apparatus a and open flames.	Aracteristics Specific Gravity (H20 = Evaporation Rate:(but) ent Odor Azard Data Flammable Limits e, Dry Chemical, Foam itainers exposed to fire.	= 1): 0.88 Va yl acetate = 1) >1 V V. s: LEL 1.0 UEL 15 Special Fire Fighting F Clear area of unprote	.O.C.: 6.51 #/gal O.C. less exempt s .0 Procedures cted personnel. Fire	olvents: 5.9 #/gal
DOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F /apor Density (Air = 1): Heavier than Air Appearance and Odor: Clear Liquid, Solve Section IV-Fire and Explosion Ha Flash Point (Method Used): <20°F (TCC) Extinguishing Media Class B extinguisher, Carbon Dioxid Water spray can be used to cool cor self-contained breathing apparatus a and open flames. Jnusual Fire and Explosion Hazards	Aracteristics Specific Gravity (H20 = Evaporation Rate:(but) ent Odor Azard Data Flammable Limits e, Dry Chemical, Foam intainers exposed to fire. and proper protection ge	= 1): 0.88 Va yl acetate = 1) >1 V V. s: LEL 1.0 UEL 15 Special Fire Fighting F Clear area of unprote ear. Keep containers cl	.O.C.: 6.51 #/gal O.C. less exempt s .0 Procedures cted personnel. Fire	olvents: 5.9 #/gal
DOT SHIPPING: FLAMMABLE LIQUID; F Section III-Physical/ChemicalCha Boiling Point: 133° F Yapor Density (Air = 1): Heavier than Air Appearance and Odor: Clear Liquid, Solve Section IV-Fire and Explosion Ha Flash Point (Method Used): <20°F (TCC) Extinguishing Media Class B extinguisher, Carbon Dioxid Water spray can be used to cool cor self-contained breathing apparatus a and open flames.	Aracteristics Specific Gravity (H20 = Evaporation Rate:(but) ent Odor Azard Data Flammable Limits e, Dry Chemical, Foam intainers exposed to fire. and proper protection ge	= 1): 0.88 Va yl acetate = 1) >1 V V. s: LEL 1.0 UEL 15 Special Fire Fighting F Clear area of unprote ear. Keep containers cl	.O.C.: 6.51 #/gal O.C. less exempt s .0 Procedures cted personnel. Fire	olvents: 5.9 #/gal

Stability – Unstable: Conditions to Avoid: Sources of ignition Stable: Yes Incompatibility (Materials to Avoid): Strong Oxidizers Hazardous Decomposition products: Carbon monoxide, Carbon dioxide, and Oxides of nitrogen Hazardous Polymerization: Will not occur

Section VI- Health Hazard Data

Routes of Entry: Inhalation? Yes Skin? Yes Ingestion? Yes

Health Hazards (Acute and Chronic)

May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible. Long-term exposure (years) vapor may cause lung, liver or kidney damage. The solvents listed have been reported to affect the central nervous system. Signs and Symptoms of Exposure: Inhalation - difficulty in breathing; Skin – redness; Ingestion - vomiting Medical Conditions Generally Aggravated by Exposure: Heart Disease; respiratory disorders.

Emergency and First Aid Procedures:

If overcome by vapors give oxygen. Do not induce vomiting. Wash eyes with large quantities of water. Wash skin with soap and water.

Carcinogenicity NTP? No IARC Monograhps? No OSHA? No

Section VII - Precautions for Safe handling and Use

Steps to be taken in Case Material is Released or Spilled- -Eliminate all sources. Scrape up with NONSPARKING tools. Remove outside area away from ignition sources. FLASHBACK POSSIBLE.

Waste Disposal Method--Dispose as hazardous waste in accordance with EPA RCRA.

Precautions to be taken in Handling and Storing- Keep away from heat, sparks or open flame. Store at temperatures below 120F

Other Precautions - -Excessive skin contact may defat skin causing dermatitis.

Respiratory Protection (Specify Type): Self contained breathing apparatus if above TLV limit exceeding.

Ventilation Local Exhaust: YES Mechanical (General)

Protective Gloves: Neoprene, Viton

Eye Protection: Wear eye protection.

Other Protective Clothing or Equipment: N/A

Work/Hygienic Practices: Do not smoke while using. Wash your hands after every use. Avoid unnecessary exposure and removal of the material from skin and clothing.

* SARA

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Super Fund Amendments and Reauthorization Act (SARA) if 1906 and 40 CFR Part 372. You must notify each person to whom this mixture or trade name product is sold. This statement must remain a part of this Material Data Safety Sheet. This statement must not be detached. Any copy or redistribution of this Material Data Safety Sheet shall include this statement.